TRACTOR PROVIDER

MASSIVE **240S - 50 HP**

MASSIVE FARM TRACTORS

PERFORMANCE

Maximum engine power at 2,250 rpm 50 hp^* Maximum torque at 1,400 rpm 172 Nm Maximum PTO power at rated 44 hp^{**} engine speed

- * Certified to BU AU 141a: (1971)
- * Manufacturer's estimate

ENGINE

AD 3,1524 Type Diesel No. Of Cylinders 3 Injection Direct Bore 91.4mm Stroke 127.0 mm Capacity 2.5 I 16.5:1 Compression ratio Natural Aspiration Starting Aid **Thermostat** Throttle control Hand and foot Cooling Water Air Cleaner Type Oil bath Air Pre-Cleaner Over Bonnet, air swirl Fuel filter Dual, high capacity Vertical **Exhaust**

ELECTRICS

\/- I4----

voitage	12 V, Negative Earth
Battery	110 Ah
Starter	2.2 kW
Alternator	32 Amp

CLUTCH

Type Dual clutch Diameter 305 x 254 mm

TRANSMISSION

Туре	Sliding Spur
Number of gears	& forward, 2 reverse
Road speed at 2,250 engine r	pm with
12.4 / 11 - 28 rear tyrea	
Gear	Speed (kph)

12.47 11 - 20 1cui tyicu		
Gear		Speed (kph)
Forward 1	(first low)	2.7
Forward 2		3.9
Forward 3		5.3
Forward 4		7.2
Forward 5	(first high)	10.6
Forward 6		15.6
Forward 7		21.3
Forward 8		28.6
Reverse 1	(low)	3.6
Reverse 2	(high)	14.5

POWER TAKE OFF

Туре	Live
Engine speed at 240 PTO rpm	1,789 rpm
Shaft diameter	35 mm
no. Of splines	6

HYDRAULICS

Functions

	Position control, Response control,
	Constant pumping
Pump Type	Reciprocating
Maximum Oil Flow	Ferguson Pump 16:/mix

Maximum Pressure	19.2 Mpa
Max. Lift capacity with	1,415 kg

Lower Links	With cat, I & II
	interchangeable balls

FRONT AXLE

lower links horizontal

Type		Box Section,
	V	Adjustable

STEERING

Steering	Hydrostatic

REAR AXLE AND BRAKES

Brake Type	Out board drum brakes
Actuation	Mechanical,
	Independent or locked
	together
Parking Brake	Hand lever operated
Differential lock	Mechanical

INSTRUMENTATION

Gauges	Technometer,
	Hourmeter, Feul level,
	Battery condition &
	Water temeprature

Warning lights	Direction indicators
	Battery charge,
	Headlight main beam,
	Low engine oil
	pressure & Brake lights

TYRES

Front	6.00 - 16 (6PR)
Rear	12.4 / 11 - 28 (6PR)

TRACK ADJUSTMENT

Front	1,245 - 1,854 m	m

Rear 1,321 - 1,930 mm

WEIGHTS AND DIMENSIONS

Weight

Draft control.

Gross Weight 1,690 kg

Dimensions

Wheel base	1,8 9 2 mm
Overall Length	3,260 mm
Overall width (min)	1,651 mm

Height

Over	exhaust	2,145 mm
Over	steering wheel	1,410 mm

Turning Circle

With brakes	5,560 mm
Without brakes	6,200 mm

Ground Clearance

Under gear box	338 mm
----------------	--------

CAPACITIES

07.1.710.111.20	
Fuel tank	47.5 I
Engine pump	6.8 I
Cooling system	10.2 I
Hydraulic system	33.0 I
Steering box	0.9 I
Oil bath air-cleaner	0.65 I

STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

OPTIONAL EQUIPMENT

Front end weights, swinging drawber, sun Canopy.