MF 240 - 50 HP

MASSEY FERGUSON

PERFORMANCE

Maximum engine power at 2,250 rpm 50 hp* Maximum torque at 1,400 rpm 172 Nm Maximum PTO power at rated 44 hp** engine speed

*Certified to BU AU 141a: (1971)

** Manufacturer's estimate

ENGINE

| Туре | Diesel | AD 3,1524 |
|-------------------|-----------|--------------|
| No. Of Cylinders | | 3 |
| Injection | | Direct |
| Bore | | 91.4mm |
| Stroke | | 127.0 mm |
| Capacity | | 2.5 I |
| Compression ratio | | 16.5 : 1 |
| Aspiration | | Natural |
| Starting Aid | 7 | hermostat |
| Throttle control | Hai | nd and foot |
| Cooling | | Water |
| Air Cleaner Type | | Oil bath |
| Air Pre-Cleaner | Over Bonn | et, air swir |
| Fuel filter | Dual, hi | gh capacity |
| Exhaust | | Vertical |

ELECTRICS

| voitage | 12 v, Negative Earth |
|------------|----------------------|
| Battery | 110 Ah |
| Starter | 2.2 kW |
| Alternator | 32 Amp |

CLUTCH

Reverse 2

Dual clutch Type Diameter 305 x 254 mm

TRANSMISSION

| Туре | Sliding Spur | |
|-------------------------------------|----------------------|--|
| Number of gears | & forward, 2 reverse | |
| Road speed at 2,250 engine rpm with | | |
| 12 4 / 11 - 28 rear tyrea | | |

| Gear | | Speed (kph) |
|-----------|--------------|-------------|
| Forward 1 | (first low) | 2.7 |
| Forward 2 | | 3.9 |
| Forward 3 | | 5.3 |
| Forward 4 | | 7.2 |
| Forward 5 | (first high) | 10.6 |
| Forward 6 | | 15.6 |
| Forward 7 | | 21.3 |
| Forward 8 | | 28.6 |
| Reverse 1 | (low) | 3.6 |

(high)

POWER TAKE OFF

| Туре | Live |
|-----------------------------|-----------|
| Engine speed at 240 PTO rpm | 1,789 rpm |
| Shaft diameter | 35 mm |
| no. Of splines | 6 |

HYDRAULICS

| Functions | Draft control, Position control, Response control, Constant pumping |
|-----------|--|
| Pump Type | Reciprocating |

| Pump Type | Recipiocating |
|-------------------------|--------------------------|
| Maximum Oil Flow | Ferguson Pump 16:/mix |
| Maximum Pressure | 19.2 Mpa |
| Max. Lift capacity with | 1,415 kg |

Lower Links With cat. I & II interchangeable balls

FRONT AXLE

lower links horizontal

Type Box Section. Adjustable

STEERING

Steering Manual

REAR AXLE AND BRAKES

| Brake Type | Out board drum brakes |
|-------------------|-----------------------|
| Actuation | Mechanical, |
| | Independent or locked |
| | together |
| Parking Brake | Hand lever operated |
| Differential lock | Mechanical |

INSTRUMENTATION

| Gauges | Technometer, |
|--------|------------------------|
| | Hourmeter, Feul level, |
| | Battery condition & |
| | Water temeprature |

Warning lights Direction indicators, Battery charge, Headlight main beam, Low engine oil pressure & Brake lights

TYRES

14.5

Front 6.00 - 16 (6PR) Rear 12.4 / 11 - 28 (6PR)

TRACK ADJUSTMENT

| Front | 1,245 - 1,854 mm |
|-------|------------------|
| | |

Rear 1,321 - 1,930 mm

WEIGHTS AND DIMENSIONS

Weight

Gross Weight 1,690 kg

Dimensions

| Wheel base | 1,892 mm |
|---------------------|----------|
| Overall Length | 3,260 mm |
| Overall width (min) | 1,651 mm |

Height

| Over | exhaust | 2,145 | mm |
|------|----------------|-------|----|
| Over | steering wheel | 1,410 | mm |

Turning Circle

| With brakes | 5,560 mm |
|----------------|----------|
| Without brakes | 6,200 mm |

Ground Clearance

| Under gear box | 338 mm |
|----------------|--------|
|----------------|--------|

CAPACITIES

| Fuel tank | 47.5 I |
|----------------------|--------|
| Engine pump | 6.8 1 |
| Cooling system | 10.2 I |
| Hydraulic system | 33.0 1 |
| Steering box | 0.9 I |
| Oil bath air-cleaner | 0.65 |
| | |

STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

OPTIONAL EQUIPMENT

Front end weights, swinging drawber, sun Canopy.