# MF 385 - 85 HP

# **MASSEY FERGUSON**

1.432 - 2.134 mm

#### **PERFORMANCE**

Maximum engine power at 2,250 rpm 85 hp\* Maximum torque at 1,400 rpm 291 Nm Maximum PTO power at rated 70 hp\*\* engine speed

\*Certified to BU AU 141a: (1971)

\*\* Manufacturer's estimate

# **ENGINE** Type

No. Of Cylinders	4
Injection	Direct
Bore	101 mm
Stroke	127 mm
Capacity	4.1
Compression ratio	15.3 : 1
Aspiration	Natura
Starting Aid	Thermostari
Throttle control	Hand and foo
Cooling	Water
Air Cleaner Type	Oil bath
Air Pre-Cleaner	Over Bonnet, air swir
Fuel filter	Dual, high capacit
Exhaust	Vertical muffle
Oil cooler	Water Cooled

# **ELECTRICS**

Voltage	12 V, Negative Earth
Battery	110 Ah
Starter	2.8 kW
Alternator	45 Amp

### CLUTCH

Type

Reverse 2

Туре	Dual clutch
Diameter	305 x 254 mm
Lining Material	Cerametallic

### **TRANSMISSION**

Number of gears

Road speed	at 2,200 engine rpm wit	h
18.4 / 15 - 30	rear tyres	
Gear		Speed (kph)
Forward 1	(first low)	2.7
Forward 2		3.7
Forward 3		5.1
Forward 4		6.8
Forward 5	(first high)	10.4
Forward 6		15.2
Forward 7		20.8
Forward 8		27.9
Reverse 1	(low)	3.5

(high)

### **POWER TAKE OFF**

Туре	Live
Engine speed at 540 PTO rpm	1,789 rpm
Shaft diameter	35 mm
no. Of splines	6

# **HYDRAULICS Functions**

**Perkins / 4.41** 

Sliding Spur

14.1

& forward, 2 reverse

	Constant pumping
Pump Type	4-Piston Ferguson Pump
Maximum Oil Flow	16.7 l / min
Maximum Pressure	21.2 Mpa at normal operating temperature
Max. Lift capacity with lower links horizontal	2,145 kg
Lower Links	With cat. I & II interchangeable balls

# **FRONT AXLE**

Туре	Box Section,
	Adjustable

### STEERING

Туре	Hydrostatic

### REAR AXLE AND BRAKES

Rear Axle	Straddle with epicyclic
	reduction
Brake Type	oil immersed,
	multi-disc
Braking Area	1,774 sq. Cm.
<b>Brakes Actuation</b>	Hydraulic
Parking Brake	Hand Lever operated

### INSTRUMENTATION

0	
Gauges	Technometer,
	Hourmeter, Feul level,
	Battery condition &
	Water temeprature
Warning lights	Direction indicators
	Battery charge,
	Headlight main beam,
	Low engine oil
	pressure & Brake lights

# TYRES

Front	7.50 - 16 (6PR)
Rear	18.4 / 15 - 30 (6PR)

### TRACK ADJUSTMENT

	1,271 - 1,001 111111
Rear	1 422 2 124 mm

### **WEIGHTS AND DIMENSIONS**

# Weight

Draft control. Position control.

Response control

Front

2,440 kg

# **Dimensions**

Wheel base	2,286 mm
Overall Length	3,760 mm
Overall width (min)	1,871 mm

# Height

Over exnaust	2,485 mm
Over steering wheel	1,781 mm

# **Turning Circle**

Vithout brakes	7,502 mm
----------------	----------

## **Ground Clearance**

J	Inder	gear	box	501	mm	

### **CAPACITIES**

Fuel tank	108.0 I
Engine pump	7.5 I
Cooling system	15.2 I
Hydraulic system	36.0 I
Hydrostatic steering reservior	2.0 1
Oil bath air-cleaner	0.7 I
Brake oil	0.25 I

#### STANDARD EQUIPMENT

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

#### **OPTIONAL EQUIPMENT**

Front end weights, swinging drawber, sun Canopy.