

**PERFORMANCE**

Maximum engine power at 2,250 rpm	85 hp*
Maximum torque at 1,400 rpm	291 Nm
Maximum PTO power at rated engine speed	70 hp**

\*Certified to BU AU 141a : (1971)

\*\* Manufacturer's estimate

**ENGINE**

Type	Perkins / 4.41
No. Of Cylinders	4
Injection	Direct
Bore	101 mm
Stroke	127 mm
Capacity	4.1 l
Compression ratio	15.3 : 1
Aspiration	Natural
Starting Aid	Thermostart
Throttle control	Hand and foot
Cooling	Water
Air Cleaner Type	Oil bath
Air Pre-Cleaner	Over Bonnet, air swirl
Fuel filter	Dual, high capacity
Exhaust	Vertical muffler
Oil cooler	Water Cooled

**ELECTRICS**

Voltage	12 V, Negative Earth
Battery	110 Ah
Starter	2.8 kW
Alternator	45 Amp

**CLUTCH**

Type	Dual clutch
Diameter	305 x 254 mm
Lining Material	Cerametalllic

**TRANSMISSION**

Type	Sliding Spur
Number of gears	& forward, 2 reverse
Road speed at 2,200 engine rpm with 18.4 / 15 - 30 rear tyres	
Gear	Speed (kph)
Forward 1 (first low)	2.7
Forward 2	3.7
Forward 3	5.1
Forward 4	6.8
Forward 5 (first high)	10.4
Forward 6	15.2
Forward 7	20.8
Forward 8	27.9
Reverse 1 (low)	3.5
Reverse 2 (high)	14.1

**POWER TAKE OFF**

Type	Live
Engine speed at 540 PTO rpm	1,789 rpm
Shaft diameter	35 mm
no. Of splines	6

**HYDRAULICS**

Functions	Draft control, Position control, Response control, Constant pumping
Pump Type	4-Piston Ferguson Pump
Maximum Oil Flow	16.7 l / min
Maximum Pressure	21.2 Mpa at normal operating temperature
Max. Lift capacity with lower links horizontal	2,145 kg
Lower Links	With cat. I & II interchangeable balls

**FRONT AXLE**

Type	Box Section, Adjustable
------	----------------------------

**STEERING**

Type	Hydrostatic
------	-------------

**REAR AXLE AND BRAKES**

Rear Axle	Straddle with epicyclic reduction
Brake Type	oil immersed, multi-disc
Braking Area	1,774 sq. Cm.
Brakes Actuation	Hydraulic
Parking Brake	Hand Lever operated

**INSTRUMENTATION**

Gauges	Technometer, Hourmeter, Feul level, Battery condition & Water tempeprature
Warning lights	Direction indicators, Battery charge, Headlight main beam, Low engine oil pressure & Brake lights

**TYRES**

Front	7.50 - 16 (6PR)
Rear	18.4 / 15 - 30 (6PR)

**TRACK ADJUSTMENT**

Front	1,271 - 1,881 mm
Rear	1,432 - 2,134 mm

**WEIGHTS AND DIMENSIONS****Weight**

Gross Weight	2,440 kg
--------------	----------

**Dimensions**

Wheel base	2,286 mm
Overall Length	3,760 mm
Overall width (min)	1,871 mm

**Height**

Over exhaust	2,485 mm
Over steering wheel	1,781 mm

**Turning Circle**

Without brakes	7,502 mm
----------------	----------

**Ground Clearance**

Under gear box	501 mm
----------------	--------

**CAPACITIES**

Fuel tank	108.0 l
Engine pump	7.5 l
Cooling system	15.2 l
Hydraulic system	36.0 l
Hydrostatic steering reservior	2.0 l
Oil bath air-cleaner	0.7 l
Brake oil	0.25 l

**STANDARD EQUIPMENT**

Weight frame without weights, standard tool box with set of tools, Top link, Top link end cat-i, Cat-I & II balls, Check chains, Spring operator's Manual

**OPTIONAL EQUIPMENT**

Front end weights, swinging drawber, sun Canopy.